# Vibroimpact mechanism in one separate case

# K. Ragulskis<sup>1</sup>, L. Ragulskis<sup>2</sup>

<sup>1</sup>Kaunas University of Technology, K. Donelaičio str. 73, LT-44249, Kaunas, Lithuania <sup>2</sup>Vytautas Magnus University, Vileikos str. 8, LT-44404, Kaunas, Lithuania <sup>1</sup>Corresponding author **E-mail:** <sup>1</sup>*kazimieras3@hotmail.com*, <sup>2</sup>*l.ragulskis@if.vdu.lt* 

Received 20 December 2018; accepted 16 May 2019 DOI https://doi.org/10.21595/mme.2019.20818

Check for updates

Copyright © 2019 K. Ragulskis, et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

**Abstract.** It is known that in the vibroimpact system at the chosen values of parameters linear relationship between impact velocities and eigenfrequencies may exist. The purpose of this paper is to reveal the qualities of the systems of this type. Investigations are performed by analytical and numerical methods. It is determined that in the systems of this type nonlinear solutions with infinite series of harmonics exist. Multivalued stable and unstable regimes do not exist in the systems. The obtained analytical relationships enabled to reveal new qualities of the systems and to make useful conclusions.

**Keywords:** characteristics of impact velocity and eigenfrequencies, free and decaying vibrations, phase trajectories of motions, harmonics of motions up to infinity.

# 1. Introduction

Investigation of dynamics of vibroimpact systems is presented in a number of publications, where the main fundamental achievements are presented including recent years for the cases when the vibrations of the system are with stiff and soft stiffness characteristics. Here the system of intermediate type is investigated. Investigations were performed also graphically, and they enabled to reveal the qualities of the system, which enable to create energetically more effective mechanisms.

Resonances and velocity jumps in nonlinear dynamics are investigated in [1]. Basic theory of vibrating systems with impacts is presented in [2]. Vibro-impact dynamics under periodic and transient excitations is investigated in [3]. Modeling of nonlinear dynamics of a system with clearance is performed in [4]. Dynamical behavior of a vibro-impact oscillator is investigated in [5]. Stabilization of periodic nonlinear systems is analysed in [6]. Basic ideas of vibrating systems in engineering are presented in [7]. Contemporary methods of vibration theory are described in [8]. Basic concepts of mechanical vibrations are presented in [9]. Nonlinear dynamics of inertial actuators is investigated in [10]. Nonlinear effects in dynamics of bearings are presented in [11]. Nonlinear contact dynamics of ultrasonic actuator is investigated in [12]. Non-sinusoidal dynamics of interacting oscillators is analysed in [13]. Free vibration analysis of piezoelectric cylinder is performed in [14]. Free vibrations of nonlinear oscillators are investigated in [15]. Synchronization of impacting mechanical systems is analysed in [16]. Chatter in mechanical systems with impacts is investigated in [17]. Dynamics of systems with impact and friction is analysed in [18]. Periodic orbits of mechanical systems with impacts are investigated in [19]. Vibro-impact nonlinear behavior and energy transfer are described in [20]. Modeling of particle impact is performed in [21]. Impacts in novel mechanisms and their applications are investigated in [22]. Resonant type impact mechanism is analysed in [23]. Positioning using impact drive mechanism is investigated in [24]. Impact mechanics of collisions and experimental results are analysed in [25]. Nonlinear rotor system with vibration absorbers is investigated in [26]. Active vibration absorber for impulse excitation is described in [27]. Nonlinear vibrations of a beam with piezoelectric actuators are investigated in [28]. Nonlinear effects and their use for vibration isolation are analysed in [29]. Nonlinear vibration absorber is investigated in [30]. Nonlinear free vibrations of beams are analysed in [31]. Electro-mechanical coupling vibrations of structures are

investigated in [32]. Nonlinear dynamic analysis of vehicle system is performed in [33]. Wideband vibration attenuation is investigated in [34]. Nonlinear vibrations with interactions are analysed in [35]. Piezoelectric nonlinear vibrations are investigated in [36]. Nonlinear analysis of free vibrations of beams is performed in [37]. Nonlocal free and forced vibrations of beams are investigated in [38]. Vibration system with nonlinear coupling is analysed in [39]. Nonlinear vibrations of a system with piecewise linear spring are investigated in [40]. Nonlinear vibrations of piezoelectric plates are analysed in [41]. Free and forced nonlinear vibrations of beams are investigated in [42]. Nonlinearities in piezoceramic actuators are analysed in [43]. Nonlinear free and forced vibrations of beams are investigated in [44]. Nonlinear free vibrations of shells are analysed in [45]. Nonlinear free vibrations of plates are investigated in [46].

The system is described in the following way:

$$m\ddot{x} + H\dot{x} + Cx = F\sin\omega t, \ x < 0, \tag{1}$$
  
$$\dot{x}^{+} = -R\dot{x}^{-}, \ x = 0, \tag{2}$$

$$\dot{x}^+ = -R\dot{x}^-, \ x = 0,$$
 (2)

where the collision of the vibrating mass is considered as an instantaneous process,  $\dot{x}^{-}$  denotes velocity before the impact and  $\dot{x}^+$  denotes velocity after the impact, the coefficient of restitution of the impact velocity of the mass is denoted as R and it is in the interval  $0 \le R \le 1$ .

The equation is rearranged:

$$\ddot{x} + 2h\dot{x} + p^2 x = f\sin\omega t, \ x < 0, \tag{3}$$

where:

$$2h = \frac{H}{m}, \ p = \sqrt{\frac{C}{m}}, \ f = \frac{F}{m}.$$

# 2. Conservative motion of the system, decaying vibrations when f = 0

It is assumed that the impact number *i* of the mass *m* to the support takes place when:

$$t = 0, \ x = 0, \ \dot{x} = \dot{x}_i > 0,$$
 (4)

and the next impact number i + 1 takes place when:

$$t = T_i, \ x = 0, \ \dot{x} = \dot{x}_{i+1} > 0.$$
 (5)

According to the Eq. (3) motion after  $t \ge 0$  is:

$$x = e^{-ht} \left( C_1 \cos \sqrt{p^2 - h^2} t + C_2 \sin \sqrt{p^2 - h^2} t \right), \tag{6}$$

where the constant quantities  $C_1$  and  $C_2$  are found from the conditions Eq. (4) by assuming  $\dot{x}_i^+$ after impact according to the Eq. (4).

Thus:

$$x = -\frac{R\dot{x}_{i}^{-}}{\sqrt{p^{2} - h^{2}}}e^{-ht}\sin\sqrt{p^{2} - h^{2}}t,$$
(7)

$$\dot{x} = -\frac{R\dot{x}_i^-}{\sqrt{p^2 - h^2}} e^{-ht} \left( -h\sin\sqrt{p^2 - h^2}t + \sqrt{p^2 - h^2}\cos\sqrt{p^2 - h^2}t \right),\tag{8}$$

VIBROIMPACT MECHANISM IN ONE SEPARATE CASE. K. RAGULSKIS, L. RAGULSKIS

$$\ddot{x} = \frac{R\dot{x}_i^-}{\sqrt{p^2 - h^2}} e^{-ht} \left[ (p^2 - h^2) \sin\sqrt{p^2 - h^2} t + 2h\sqrt{p^2 - h^2} \cos\sqrt{p^2 - h^2} t \right].$$
(9)

The next impact number i + 1 takes place at the conditions Eq. (5). By taking into account the Eqs. (7) and (8) it is obtained:

$$T_i = \frac{\pi}{\sqrt{p^2 - h^2}} \tag{10}$$

During the time of the cycle of motion between the impacts i and i + 1 the change of velocities is lost, which is estimated by the dummy coefficient:

$$R_{f_{i+1,i}} = \frac{\dot{x}_{i+1}}{\dot{x}_{i}} = +R \cdot \exp\left(-\frac{h}{\sqrt{p^2 - h^2}}\pi\right) = -R \cdot \exp\left(\frac{h/p}{\sqrt{1 - (h/p)^2}}\right).$$
(11)

Further graphical material representing dynamics of the investigated system is presented for various parameters of the system in Fig. 1, Fig. 2 and Fig. 3.





VIBROIMPACT MECHANISM IN ONE SEPARATE CASE. K. RAGULSKIS, L. RAGULSKIS



(line of medium thickness) and t = 0, x(0) = -1/3 (thick line)

# 3. Dynamics of the conservative system

Case: conservative system, that is when:

$$h = f = 0, R = 1.$$
 (12)

In this case the Eqs. (7)-(10) take the following form when:

 $\begin{aligned} x < 0, \tag{13} \\ x = -\frac{\dot{x}^{-}}{p} \operatorname{sinpt}, \tag{14} \\ \dot{x} = -\dot{x}^{-} \operatorname{cospt}, \tag{15} \\ \ddot{x} = \dot{x}^{-} p \operatorname{sinpt}, \tag{16} \\ \overline{T} = -\frac{\pi}{p}. \tag{17} \end{aligned}$ 

Period of motion  $\overline{T}$  is the eigenperiod of vibrations of the system and  $\overline{\omega}$  is the eigenfrequency

of vibrations of the system, that is by equating the right sides of the Eqs. (17) it is obtained:



By expanding the functions of displacement, velocity and acceleration into the Fourier series the following expressions of the first terms of the series are obtained. The laws of motions may be expanded into the Fourier series. From the Eqs. (14-16) it is obtained:

$$x = -\frac{\dot{x}^{-}}{p} \left\{ \frac{2}{\pi} - \frac{4}{\pi} \sum_{n=1}^{n=\infty} \left[ \frac{1}{(2n-1)(2n+1)} \cos n\overline{\omega}t \right] \right\},\tag{19}$$

$$\dot{x} = -\dot{x}^{-} \frac{8}{\pi} \sum_{n=1}^{n=\infty} \left[ \frac{n}{(2n-1)(2n+1)} \sin n \overline{\omega} t \right],$$
(20)

$$\ddot{x} = p\dot{x}^{-} \left\{ \frac{2}{\pi} - \frac{4}{\pi} \sum_{n=1}^{n=\infty} \left[ \frac{1}{(2n-1)(2n+1)} \cos n\overline{\omega}t \right] \right\},\tag{21}$$

where  $\overline{\omega} = 2p$ .

From the Eqs. (14) and (15) it is obtained:

$$\dot{x}^2 + (px)^2 = (\dot{x}^-)^2, \tag{22}$$

that is in the system of coordinates  $\dot{x}0px$  there is a circle the length of radius of which is equal to  $\dot{x}^{-}$ .

From the Eqs. (15) and (16) it is obtained:

$$\left(\frac{\ddot{x}}{p}\right)^2 + \dot{x}^2 = (\dot{x}^-)^2,$$
(23)

that is in the system of coordinates  $\frac{\ddot{x}}{p}0\dot{x}$  there is a circle the length of radius of which is equal to  $\dot{x}^-$ .

Further graphical material of amplitude frequency characteristics is presented in Fig. 4.





#### 4. Conclusions

On the basis of the presented results the qualities of dynamic behavior of the nonlinear vibroimpact mechanism in separate case, when the contacting surface of the vibrating part of the system with the impacting surface is in the position of static equilibrium, are investigated.

Analytical relationships describing the motion of the system and amplitude frequency characteristics have been determined and are presented in the paper. Graphical relationships for typical parameters of the system were obtained and are investigated. It is shown that the values of eigenfrequencies of vibroimpact vibrations do not depend on the values of amplitudes of excitations. Because of this fact multivalued stable and unstable regimes can not take place in the vicinities of resonances.

The presented results enable to perform the design of vibrating vibroimpact systems of this type.

# References

- [1] Wedig W. V. New resonances and velocity jumps in nonlinear road-vehicle dynamics. Procedia IUTAM, Vol. 19, 2016, p. 209-218.
- [2] Ragulskienė V. Vibro-Shock Systems (Theory and Applications). Mintis, Vilnius, 1974, (in Russian).
- [3] Li T., Gourc E., Seguy S., Berlioz A. Dynamics of two vibro-impact nonlinear energy sinks in parallel under periodic and transient excitations. International Journal of Non-Linear Mechanics, Vol. 90, 2017, p. 100-110.
- [4] Wang Y., Li F.-M. Nonlinear dynamics modeling and analysis of two rods connected by a joint with clearance. Applied Mathematical Modelling, Vol. 39, Issue 9, 2015, p. 2518-2527.
- [5] Fu Y., Ouyang H., Davis R. B. Nonlinear dynamics and triboelectric energy harvesting from a three-degree-of-freedom vibro-impact oscillator. Nonlinear Dynamics, Vol. 92, 2018, p. 1985-2004.
- [6] Zaitsev V. A. Global asymptotic stabilization of periodic nonlinear systems with stable free dynamics. Systems and Control Letters, Vol. 91, 2016, p. 7-13.
- [7] Bolotin V. V. Vibrations in Engineering. Handbook, Vol. 1. Mashinostroienie, Moscow, 1978, (in Russian).
- [8] Inman D. J. Vibration with Control, Measurement, and Stability. Prentice-Hall, New Jersey, 1989.
- [9] Lalanne M., Berthier P., Der Hagopian J. Mechanical Vibrations for Engineers. John Wiley and Sons, New York, 1984.
- [10] Borgo M. D., Tehrani M. G., Elliott S. J. Identification and analysis of nonlinear dynamics of inertial actuators. Mechanical Systems and Signal Processing, Vol. 115, 2019, p. 338-360.
- [11] Peixoto T. F., Cavalca K. L. Investigation on the angular displacements influence and nonlinear effects on thrust bearing dynamics. Tribology International, Vol. 131, 2019, p. 554-566.
- [12] Geetha G. K., Mahapatra D. R. Modeling and simulation of vibro-thermography including nonlinear contact dynamics of ultrasonic actuator. Ultrasonics, Vol. 93, 2019, p. 81-92.
- [13] Dellavale D., Rossello J. M. Cross-frequency couplings in non-sinusoidal dynamics of interacting oscillators: acoustic estimation of the radial position and spatial stability of nonlinear oscillating bubbles. Ultrasonics Sonochemistry, Vol. 51, 2019, p. 424-438.
- [14] Rabbani V., Bahari A., Hodaei M., Maghoul P., Wu N. Three-dimensional free vibration analysis of triclinic piezoelectric hollow cylinder. Composites Part B: Engineering, Vol. 158, 2019, p. 352-363.
- [15] Qu H., Li T., Chen G. Multiple analytical mode decompositions (M-AMD) for high accuracy parameter identification of nonlinear oscillators from free vibration. Mechanical Systems and Signal Processing, Vol. 117, 2019, p. 483-497.
- [16] Baumann M., Biemond J. J. B., Leine R. I., Wouw N. V. D. Synchronization of impacting mechanical systems with a single constraint. Physica D: Nonlinear Phenomena, Vol. 362, 2018, p. 9-23.
- [17] Dankowicz H., Fotsch E. On the analysis of chatter in mechanical systems with impacts. Procedia IUTAM, Vol. 20, 2017, p. 18-25.
- [18] Pournaras A., Karaoulanis F., Natsiavas S. Dynamics of mechanical systems involving impact and friction using an efficient contact detection algorithm. International Journal of Non-Linear Mechanics, Vol. 94, 2017, p. 309-322.
- [19] Spedicato S., Notarstefano G. An optimal control approach to the design of periodic orbits for mechanical systems with impacts. Nonlinear Analysis: Hybrid Systems, Vol. 23, 2017, p. 111-121.
- [20] Li W., Wierschem N. E., Li X., Yang T. On the energy transfer mechanism of the single-sided vibro-impact nonlinear energy sink. Journal of Sound and Vibration, Vol. 437, 2018, p. 166-179.
- [21] Marshall J. S. Modeling and sensitivity analysis of particle impact with a wall with integrated damping mechanisms. Powder Technology, Vol. 339, 2018, p. 17-24.
- [22] Esa M., Xue P., Kassem M., Abdelwahab M., Khalil M. Manipulation of impact feedbacks by using novel mechanical-adaptor mechanism for UAV undercarriage applications. Aerospace Science and Technology, Vol. 70, 2017, p. 233-243.
- [23] Yokozawa H., Doshida Y., Kishimoto S., Morita T. Resonant-type smooth impact drive mechanism actuator using lead-free piezoelectric material. Sensors and Actuators A: Physical, Vol. 274, 2018, p. 179-183.
- [24] Tan Y., Lu P., Zu J., Zhang Z. Large stroke and high precision positioning using iron-gallium alloy (Galfenol) based multi-DOF impact drive mechanism. Precision Engineering, Vol. 49, 2017, p. 401-411.

- [25] Zhang S., Villavicencio R., Zhu L., Pedersen P. T. Impact mechanics of ship collisions and validations with experimental results. Marine Structures, Vol. 52, 2017, p. 69-81.
- [26] Taghipour J., Dardel M., Pashaei M. H. Vibration mitigation of a nonlinear rotor system with linear and nonlinear vibration absorbers. Mechanism and Machine Theory, Vol. 128, 2018, p. 586-615.
- [27] Wang X., Yang B. Transient vibration control using nonlinear convergence active vibration absorber for impulse excitation. Mechanical Systems and Signal Processing, Vol. 117, 2019, p. 425-436.
- [28] Przybylski J., Gasiorski G. Nonlinear vibrations of elastic beam with piezoelectric actuators. Journal of Sound and Vibration, Vol. 437, 2018, p. 150-165.
- [29] Feng X., Jing X. Human body inspired vibration isolation: beneficial nonlinear stiffness, nonlinear damping & nonlinear inertia. Mechanical Systems and Signal Processing, Vol. 117, 2019, p. 786-812.
- [30] Feudo S. L., Touze C., Boisson J., Cumunel G. Nonlinear magnetic vibration absorber for passive control of a multi-storey structure. Journal of Sound and Vibration, Vol. 438, 2019, p. 33-53.
- [31] Tang Y., Lv X., Yang T. Bi-directional functionally graded beams: asymmetric modes and nonlinear free vibration. Composites Part B: Engineering, Vol. 156, 2019, p. 319-331.
- [32] Li H., Wang X., Chen J. Nonlinear electro-mechanical coupling vibration of corrugated graphene/piezoelectric laminated structures. International Journal of Mechanical Sciences, Vol. 150, 2019, p. 705-714.
- [33] Zhou S., Li Y., Ren Z., Song G., Wen B. Nonlinear dynamic analysis of a unilateral vibration vehicle system with structural nonlinearity under harmonic excitation. Mechanical Systems and Signal Processing, Vol. 116, 2019, p. 751-771.
- [34] Silva T. M. P., Clementino M. A., Marqui C. D., Erturk A. An experimentally validated piezoelectric nonlinear energy sink for wideband vibration attenuation. Journal of Sound and Vibration, Vol. 437, 2018, p. 68-78.
- [35] Miyake S., Ozaki R., Hosaka H., Morita T. High-power piezoelectric vibration model considering the interaction between nonlinear vibration and temperature increase. Ultrasonics, Vol. 93, 2019, p. 93-101.
- [36] Ozaki R., Liu Y., Hosaka H., Morita T. Piezoelectric nonlinear vibration focusing on the second-harmonic vibration mode. Ultrasonics, Vol. 82, 2018, p. 233-238.
- [37] Lv Z., Qiu Z., Zhu J., Zhu B., Yang W. Nonlinear free vibration analysis of defective FG nanobeams embedded in elastic medium. Composite Structures, Vol. 202, 2018, p. 675-685.
- [38] Trabelssi M., El-Borgi S., Fernandes R., Ke L. L. Nonlocal free and forced vibration of a graded Timoshenko nanobeam resting on a nonlinear elastic foundation. Composites Part B: Engineering, Vol. 157, 2019, p. 331-349.
- [39] Huang Z., Song G., Li Y., Sun M. Synchronous control of two counter-rotating eccentric rotors in nonlinear coupling vibration system. Mechanical Systems and Signal Processing, Vol. 114, 2019, p. 68-83.
- [40] Ranjbarzadeh H., Kakavand F. Determination of nonlinear vibration of 2DOF system with an asymmetric piecewise-linear compression spring using incremental harmonic balance method. European Journal of Mechanics A/Solids, Vol. 73, 2019, p. 161-168.
- [41] Zeng S., Wang B. L., Wang K. F. Nonlinear vibration of piezoelectric sandwich nanoplates with functionally graded porous core with consideration of flexoelectric effect. Composite Structures, Vol. 207, 2019, p. 340-351.
- [42] Rouhi H., Ebrahimi F., Ansari R., Torabi J. Nonlinear free and forced vibration analysis of Timoshenko nanobeams based on Mindlin's second strain gradient theory. European Journal of Mechanics – A/Solids, Vol. 73, 2019, p. 268-281.
- [43] Shivashankar P., Kandagal S. B. Characterization of elastic and electromechanical nonlinearities in piezoceramic plate actuators from vibrations of a piezoelectric beam. Mechanical Systems and Signal Processing, Vol. 116, 2019, p. 624-640.
- [44] Mohamed N., Eltaher M. A., Mohamed S. A., Seddek L. F. Numerical analysis of nonlinear free and forced vibrations of buckled curved beams resting on nonlinear elastic foundations. International Journal of Non-Linear Mechanics, Vol. 101, 2018, p. 157-173.
- [45] Dong Y. H., Zhu B., Wang Y., Li Y. H., Yang J. Nonlinear free vibration of graded graphene reinforced cylindrical shells: effects of spinning motion and axial load. Journal of Sound and Vibration, Vol. 437, 2018, p. 79-96.
- [46] Gao K., Gao W., Chen D., Yang J. Nonlinear free vibration of functionally graded graphene platelets reinforced porous nanocomposite plates resting on elastic foundation. Composite Structures, Vol. 204, 2018, p. 831-846.